

~~_____ "Machine and method for producing cardboard tubes."
SPECIFICATION~~

_____ Docket #72130

MACHINE AND METHOD FOR PRODUCING CARDBOARD TUBES

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] _____ This application is a United States National Phase application of International
Application PCT/IT2005/000046 and claims the benefit of priority under 35 U.S.C. § 119 of
Italian application FI2004A000046 filed 24/Feb./2004, the entire contents of which are
5 incorporated herein by reference.

FIELD OF THE INVENTION

[0002] _____ The present invention ~~relates~~pertains to a machine and a method for producing
cardboard tubes.

BACKGROUND OF THE INVENTION

[0003] _____ It is known that a machine for producing cardboard tubes basically comprises:

[0004] _____ - means for continuously feeding two or more ribbons made of paper or similar material, at least one ribbon being provided with a predetermined amount of glue in

5 correspondence of one of its sides, the ribbons being drawn from corresponding bobbins which are supported by the feeding means;

[0005] _____ - belt type means, which are positioned downstream of ~~said~~the feeding means, for winding and advancing ~~said~~the ribbons onto a spindle, forming a plurality of spirals which are overlapped and staggered according to a predetermined staggering step, so that the tube results

10 from the reciprocal overlapping and gluing of the ribbons which are spirally wound on the spindle;

[0006] _____ - means, which are positioned downstream of ~~said~~the spindle, for cutting the continuous tube into elements having a predetermined length.

[0007] _____ The first ribbon, i. e. the ribbon destined to directly contact the spindle, is not glued, to avoid its adhesion to the spindle surface.

15 **[0008]** _____ In practice, the belt means, which are positioned onto the spindle downstream of with respect to the feeding direction of the ribbons, drawn the ribbons by exerting on them a traction force which is directed towards the spindle and, while it is forming, the tube made by the

overlapped spiral ribbons advances and rotates about the longitudinal axis of the spindle.

[0009]_____The intervention rate of the cutting means depends on the advancing speed of the tube onto the spindle and on the predetermined length of the elements obtained from the tube.

[0010]_____Such a machine is described in WO 95/10400 and WO 95/10399.

5 **[0011]**_____One of the main drawbacks deriving from of such machines lies in a cleavage of the tube in correspondence of the cut sections. This drawback is even more evident when the operative speed of the machine increases.

SUMMARY OF THE INVENTION

[0012]_____The main aim of the present invention is to eliminate ~~the said~~is drawback.

10 **[0013]**_____This result has been achieved, according to the invention, by ~~adopting the principles of the independent claims:~~

~~Further characteristics being set forth in the dependent claims:~~

a method for producing cardboard tubes by winding a plurality of ribbons onto a spindle, where a preset number of the ribbons are glued in correspondence of the lower surface thereof. A

15 predetermined amount of supplementary quick setting glue is applied on the lower surface of the last ribbon destined to be wound on the spindle. This supplementary glue is arranged in proximity

to at least a longitudinal edge of the ribbon forming a corresponding stripe of quick setting glue
astride or adjacent a section (ST) of the ribbon. This section (ST) is arranged to be acted on by a
subsequent cutting action executed downstream of the spindle. The application of the at least one
stripe of supplementary glue is operated at intervals corresponding to a preset length of the last
ribbon.

[0014] The present invention also relates to a cardboard tube producing machine, with a
structure supporting feeding means for a plurality of ribbons of paper or paper-like material, and a
spindle. The ribbons are wound on the spindle. The ribbons are glued in correspondence of the
respective lower surfaces, with the exception of the first ribbon which is destined to the direct
contact with the spindle. Means are provided for moving the ribbons and winding them on the
spindle. The machine also comprises supplementary glue means disposed and acting along a path
of the ribbon, the upper surface of which is destined to define the outer surface of a tube. The
supplementary glue means distributes a stripe of supplementary quick setting glue in proximity to
almost a longitudinal edge of the lower surface of the ribbon astride of a section of the latter
interested by a subsequent cutting operation downstream of the spindle. The supplementary glue
means being operated at intervals corresponding to a present length of the last ribbon.

[0015] Thanks to the present invention, it is possible to increase the operative speed of the
machine, i.e. the feeding speed of the ribbons and, consequently, the tubes producing speed,
without the aforesaid cleavage effect.

[0016] Furthermore, a machine according to the present invention is relatively simple to make, cost-effective and reliable even after a prolonged service life and it may also be realized by modifying the existing machines, without adversely affecting the functionality thereof, at a cost which is very low when compared with the advantages which are obtained.

5 ~~These and other~~

[0017] The various features of novelty which characterize the invention are pointed out with particularity in the claims annexed to and forming a part of this disclosure. For a better understanding of the invention, its operating advantages and ~~characteristics~~ specific objects attained by its uses, reference is made to the accompanying drawings and descriptive matter in
10 which preferred embodiments of the invention will be best understood by anyone skilled in the art from a reading of the following description in conjunction with the attached drawings given as a practical exemplification of the invention, but not to be considered in a limitative sense, wherein:
 =are illustrated.

BRIEF DESCRIPTION OF THE DRAWINGS

15 In the drawings:

[0018] Fig. 1 is a partial perspective view of a machine according to the present invention;

~~–~~[0019] Fig. 2 shows a view of a particular area, represented in perspective view from the bottom, relating to the injectors for the application of the glue on the lower surface of the second ribbon treated in the machine of Fig. 1;

–[0020]_____ Fig. 3 is a schematic view of the lower surface of a portion of the second ribbon treated in the machine of Fig. 1, in which, in particular, is shown the relative position of two gluing lines;

=

5 [0021]_____ Fig. 4 is a schematic plan view of a tube portion obtained by the spiral winding of two ribbons of the same width, in which, in particular, are shown the two gluing lines of Fig. 3;

–[0022]_____ Fig. 5 ~~shows~~is a schematic plan view of two ribbons of different width at the entrance of the section of the machine comprising the spindle: in the figure is shown a gluing line applied on the lower surface of the wider upper ribbon, even if this line is on the other face of
10 the sheet;

=

[0023]_____ Fig. 6 is a schematic plan view of a tube portion obtained by the winding of the two ribbons of Fig. 5;

–[0024]_____ Fig. 7 is a simplified block diagram of the control system driving the means
15 for applying a supplementary amount of quick setting glue;

=

[0025]_____ Fig. 8 is a schematic representation relating to the cleavage of a conventional cardboard tube in correspondence of an end section;

–[0026]_____ Fig. 9 is a representation similar to that of Fig. 8 but referred to a

cardboard tube obtained according to the present invention.

~~Reduced to its basic structure, reference being made to the enclosed drawings~~

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0027] Referring to the drawings in particular, a machine according to the present

5 invention comprises, similarly to the conventional machines:

~~-[0028]~~ _____ - a structure (S) supporting a plurality of bobbins (not shown for sake of simplicity) from which are unwound more ribbons (U, L) of paper or paper-like material;

~~-[0029]~~ _____ - a plurality of gluing rolls (not shown for sake of simplicity) which are disposed downstream of ~~said~~the bobbins in respect to the advancing direction (X) of the ribbons (U,L) along a wall of ~~said~~the structure (S) and which are feed by corresponding tanks (also not shown for sake of simplicity) containing liquid glue, for applying a predetermined amount of glue on the lower surface of each of the advancing ribbons (U, L), with the exception of the first ribbon_(L), ~~i~~i. e. with the exception of the ribbon_(L), the lower surface of which is destined to the direct contact with a spindle {1} disposed downstream, on which the tubes are formed;

10

[0030] _____ - a spindle {1} which is longitudinally developed along the direction of the tube to be produced, the ribbons (U, L) being wound onto ~~said~~the spindle forming a plurality of superimposed and staggered spirals;

15

-[0031]_____ - belt: means (2), with relevant motor means (20), for spirally winding said the ribbons (U, L) onto the spindle (1) and advancing the forming tube along the longitudinal axis (m-m) of the same spindle 1;

[0032]_____ cutting means (not shown for sake of clarity) for subdividing the tube (T) into portions or tubular elements having a predetermined length.

[0033]_____ As stated above, the feeding and gluing means acting on the ribbons (U, L), the winding means and the means for cutting the tube (which results from the overlapping and reciprocal gluing of the ribbons spirally wound onto the spindle) are known to those skilled in the art and, therefore, it is omitted a more detailed description thereof. The gluing of the lower surface of the ribbons (U, L) is made, according to a known technique, upstream of the spindle (1), by means of liquid glue, the liquid glue exploiting its adhesive power in a relatively long time to avoid that it became dry along the path between the gluing station (i.e. the station where the tanks containing the liquid glue are positioned) and the spindle (1).

[0034]_____ The machine comprises means (3) for applying a predetermined amount of supplementary glue of the quick setting type to the lower surface (i.e. the surface destined to look at the spindle 1) of at least one of the ribbons which are wound onto the spindle (1) and, more precisely, to the lower surface of the last ribbon, i.e. that ribbon the upper surface of which defines the external surface of the tube.

Said **[0035]** _____ The means (3) are connected to a tank for the quick setting glue which, for sake of simplicity, is not shown in the enclosed drawings.

[0036] _____ The wording "quick setting glue" denotes a glue having a high adhesive power acting in a short time.

5 **[0037]** _____ With reference to the examples shown in the enclosed drawings, the means (3) distribute the quick setting glue on the lower surface of the second ribbon (U), which is the last ribbon and travels along a path overhanging the advancing path of the first ribbon (L), the tube being constituted by only two ribbons spirally wound and superimposed.

[0038] _____ When the ribbons are three instead of two, ~~said the~~ means (3) distribute the glue on
10 the lower surface of the third ribbon, i.e. always on the lower surface of the last ribbon.

[0039] _____ According to the example shown in the drawings, ~~said the~~ means (3) comprise a distributor apt to distribute "hot melt" glue, whose body is solid to ~~said the~~ structure (S), in such a manner to result downstream of ~~said the~~ gluing rolls and upstream of the spindle (1). ~~Said The~~
distributor (3) comprises a couple of injectors (30) fixed to a plate (32) 1 solid to the structure (S)
15 near the exit section of the latter, with the respective nozzles (31) directed to the lower surface (UV) of the ribbon to be treated (in the example, the lower surface of the second ribbon U). In correspondence with ~~said the~~ injectors (30), the ribbon (U) to be treated is kept in guide by a wing (33) of the ~~said~~ plate (32) 1 oriented parallel to the advancing direction (X) of the ribbon and

which is spaced from the nozzles (31) of the two injectors (30) in such a manner that the ribbon (U) passes through the space between the wing (33) and the nozzles (31), with the upper surface turned towards the wing (33) and the lower surface (UV) turned towards the nozzles (31).

~~Said~~The injectors (30) are disposed and acting in such a manner to distribute a preset amount of

5 quick setting glue (for example, a "hot melt" glue) in correspondence of at least one of the longitudinal edges of the lower surface (UV) of the ribbon (U) advancing towards the spindle (1).

Preferably, the injectors (30) distribute a preset amount of quick setting glue in proximity to both

the longitudinal edges (BU) of the last ribbon (U) if this has the same width of the underlying ribbon (L) and in correspondence of only one edge (BU) if the upper ribbon (U) has a greater

10 width than the lower ribbon (L). Obviously, also in the second case it is possible to distribute quick setting glue on both the longitudinal edges of the upper ribbon or last ribbon (U).

[0040] Referring to the first of the two examples, i.e. when the two ribbons (U) and (L)

have the same width, the injectors (30) are activated, for a preset time, in such a manner to apply two stripes of quick setting glue (G) on the lower surface (UV) of the last ribbon (U) astride of a

15 section (ST) subsequently involved by the action of the cutting means acting downstream of the

spindle (1). ~~Said~~The section (ST) is, as more clearly shown in Fig. 3, inclined of a preset angle (5)

in respect to the longitudinal axis (u-u) of the ribbon (U). ~~Said~~The angle (6δ) is the

complementary of the angle formed by the plan projection of the longitudinal axis of each ribbon

(L, U) with the longitudinal axis (m-m) of the spindle (1) when the ribbons are wound on the

20 latter (see Fig. 4); furthermore, this angle corresponds to the angle formed by each stripe of quick setting glue (G) with ~~said~~the section (ST).

[0041] _____ As shown in Fig. 4, when the tube formed by the spirals of the ribbons (U, L) wound on the spindle (1) is cut, since the cut is operated in correspondence of the section interested or arranged by the stripes of quick setting glue (G), both the stripes (G) are cut and a portion of each of them is both upstream and downstream of the cutting section.

5 **[0042]** _____ Therefore, when the cut is executed, both upstream and downstream of the section (ST) the corresponding edges of the ribbons (U, L) are strongly anchored to each other. In this way, it is avoided the cleavage phenomenon characteristic of the tubes produced by the conventional machines, schematically represented in Fig. 8, where "SF" denotes an edge of the last ribbon detached from the underlying ribbon in correspondence of an end section of the tube, i.e. e. in correspondence of the section interested or arranged by ~~said~~ the cut. On the contrary, as shown

10 in Fig. 9. a tube (T) according to the present invention is exempt from such phenomenon.

[0043] _____ Referring to the second example, since the last ribbon (U), i.e. the ribbon whose upper surface defines the outer surface of the tube (T), is wider than the underlying ribbon (L), it can be sufficient to distribute a preset amount of supplementary quick setting glue in

15 correspondence of only one of its longitudinal edges (BU).

[0044] _____ In the scheme or embodiment of Fig. 5, the glue stripe (G) is represented with continuous line, even if it is on the opposite face of the sheet and it is in proximity to the right edge (BU) of the ribbon (U). In the scheme of Fig. 6, the discontinuous lines marked by the reference (BL) correspond to the coinciding edges of the lower ribbon (L), spirally wound on the

spindle (1) and the glue stripe (G) is represented with continuous line, even if it is on the lower surface of the last ribbon (U), for a better highlight of the same.

[0045] _____ When only one supplementary glue stripe (G) is to be applied, then it is activated only the corresponding injector (30) instead of both the injectors.

5 **[0046]** _____ Therefore the two injectors (30) are placed in such a way to have the respective nozzle (31) disposed on the plane defined by the said section (ST) and are activated at the same time for applying two stripes of quick setting glue (G) astride of the section (ST).

[0047] _____ The distance between the nozzles (31) of the two injectors (30) depends on the width (LA) of the ribbon (U).

10 **[0048]** _____ The activation of the injectors (30) is operated on the basis of the length of the completed tubes to be produced, i.e. in function of the length of the tubes obtained from the cutting of the ribbons wound and glued spirally on the spindle (1). For example, calling "LA" the width of the ribbon (U), "D" the diameter of the spindle and "LT" the length of the tube to be produced, the injectors (30) are activated for a preset time when in correspondence of them
15 passes a portion of ribbon (U) of length equal to $LT \cdot D \cdot n / LA$ to $LT \cdot D \cdot n / LA$. The activation time of the injectors is preset on the basis of the desired length of each stripe of supplementary quick setting glue (G).

[0049] _____ The control of the amount of ribbon (U) which advances in front of the nozzles (31) of the injectors (30) can be operated by means of an encoder (4) mounted on the axis of an idly roll having a surface covered by friction= material; the ribbon passes on this surface, around the roll and determines the rotation of the same roll. _This control system, disposed upstream of the means (3), is well known in the technical field. ~~Said~~The encoder (4) is connected with a programmable electronic unit (5) apt to receive the data from the encoder (4) for processing them on the basis of the formula previously indicated and apt to operate the activation of the injectors (30) when the preset length value is reached. The structure and the working of ~~said~~the electronic control means are ~~K~~nknown by the technicians of the industrial automation and, therefore, aren't described in detail.

[0050] _____ According to present invention, an operational method involves to apply, in addition to the glue normally used for obtaining the reciprocal attachment of the two ribbons (U, L) spirally wound, a preset amount of supplementary quick setting glue (for example, a "hot melt" glue) in correspondence of the interface between the penultimate ribbon and the last one, astride of a section (ST) subsequently interested by the action of the cutting means downstream of the spindle (1).

[0051] _____ Practically, all the construction details may vary in any equivalent way as far as the shape, dimensions, elements disposition, nature of the used materials are concerned, without nevertheless departing from the scope of the adopted solution idea and, thereby, remaining within the limits of the protection granted to the present patent for invention.

[0052] While specific embodiments of the invention have been shown and described in detail to illustrate the application of the principles of the invention, it will be understood that the invention may be embodied otherwise without departing from such principles.

72130-8